

MINI SKIDSTEER



LIVING COUNTRY

EQUIPMENT FOR RURAL PROPERTY CARE

THE COMPACT SKIDSTEER

The MK Martin line of compact skidsteers provides a large-scale solution with minimal impact to your site. Tight spaces are now easily accessible and don't require larger, heavier machinery. With a large selection of attachments to choose from, the MK Martin compact skidsteer is the ideal carrier for landscapers, farmers, contractors and rural property owners.



SL WHEELED SERIES



SL11E ELECTRIC



SL21D DIESEL



SL22 GAS



TL TRACKED SERIES



TL11E ELECTRIC



TL21D DIESEL



TL22 GAS



SL21D DIESEL



SL21D	Standard Setup
Engine	Kubota D722-E4B
Capacity (kW/Hp)	14.9/20.3
Start up	Electric
Number of Cylinders	3
Revolutions per minute (RPM)	3600
Cooling	Air cooled
Fuel/ Fuel Tank Capacity	Diesel/ 25 (L) 6.60 (gallons)
Drive System	Hydraulic 4WD wheel motors
Speed (KM/H)	0-7 (proportional)
Hydraulic Drive System	10.5 GPM / 2750 PSI
Hourmeter	Standard
Hydraulic Tank Capacity	25 (L) 6.60 (gallons)
Standard Wheels	23x8.50-12 Skid
Electrical System (V)	12
Battery Capacity(Ah)	45
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	749.57 (with counterweights)
Lift Height to Pin (in.)	83
Traction force (LBS)	1102.31 (with counterweights)
Breakout force (LBS)	705.48
Dimensions (L in. x W in. x H in.)	60.04x38.39x49.53
Weight (LBS)	1521.19
Case Drain	Included

SL22 GAS



SL22	Standard Setup
Engine	HONDA HGX690
Capacity (KW/HP)	16.5 / 22.1
Start up	Electric
Displacement cm3/ Number of Cylinders	688/2
Revolutions per minute (RPM)	3600
Cooling	Air cooled
Fuel/ Fuel Tank Capacity	Gasoline / 15 (L) 3.96 (gallons)
Drive System	Hydraulic 4WD wheel motors
Speed (KM/H)	0-7 (proportional)
Hydraulic Drive System	11.8 GPM / 2750 PSI
Hourmeter	Standard
Hydraulic Tank Capacity	44 (L) 11.62 (gallons)
Standard Wheels	22X11.00-8 All Trac
Electrical System (V)	12
Battery Capacity(Ah)	45
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	771.62 (with counterweights)
Lift Height to Pin (in.)	82.5
Traction Force (LBS)	1102.31 (with counterweights)
Breakout Force (LBS)	705.48
Dimensions (L in. x W in. x H in.)	60.04x38.39x49.53
Weight (LBS)	1388.91
Case Drain	Included

SL11E ELECTRIC



SL11E	Standard Setup
Motor	Dana Electric Motor
Revolutions per minute (RPM)	2500
Battery Type	Traction battery
Voltage (V)	36
Battery Capacity (Ah)	240
Engine Power (KW)	5.7
Drive System	Hydraulic 4WD wheel motors
Speed	4.9 km/h / 3.045 mph
Hydraulic Drive System	4.86 GPM
Hourmeter	Standard
Hydraulic Tank Capacity	18 (L) 4.76 (gallons)
Standard Wheels	4.00-8 Forklift
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	992.08 (with counterweights)
Lift Height to Pin (in.)	80.4
Traction Force (LBS)	859.80 (with counterweights)
Breakout Force (LBS)	881.85
Dimensions (L in. x W in. x H in.)	60.04x29.13x49.21
Weight (LBS)	1873.93
Charger (apart)	
Electronic charger (code 48161020)	220V

SL SERIES OPTIONS

- Case Drain (SL11E)
- Floating System
- Electric Floating Systems
- Integrated Counterweights (50kg)
- Side Counterweights (30kg)
- Electric Socket + Flow Diverter Kit
- High Power Wheel Motor
- Canister Filter
- Toro Plate Adapter



TL21D DIESEL



Model available also with remote control.

TL21D	Standard Setup
Engine	KUBOTA D722-E48
Capacity (KW/HP)	14.9/20.3
Start up	Electric
Number of Cylinders	3
Revolutions per minute (RPM)	3600
Cooling	Air cooled
Fuel/ Fuel Tank Capacity	Diesel/ 25 (L) 6.60 (gallons)
Drive System	Hydraulic 4WD wheel motors
Speed (KM/H)	0-7 (proportional)
Hydraulic Drive System	10.5 GPM / 2750 PSI
Hourmeter	Standard
Hydraulic Tank Capacity	25 (L) 6.60 (gallons)
Standard Wheels	180 mm Rubber Tracks
Electrical System (V)	12
Battery Capacity(Ah)	45
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	749.57 (with counterweights)
Traction Force (LBS)	1543.24 (with counterweights)
Breakout Force (LBS)	705.48
Dimensions (L in. x W in. x H in.)	60.04x41.34x51.38
Weight (LBS)	1962.11
Case Drain	Included

TL22 GAS



TL22	Standard Setup
Engine	HONDA HGX690
Capacity (KW/HP)	16.5 / 22.1
Start up	Electric
Displacement cm3/ Number of Cylinders	688/2
Revolutions per minute (RPM)	3600
Cooling	Air cooled
Fuel/ Fuel Tank Capacity	Gasoline / 15 (L) 3.96 (gallons)
Drive System	Hydraulic 4WD wheel motors
Speed (KM/H)	0-7 (proportional)
Hydraulic Drive System	11.8 GPM / 2750 PSI
Hourmeter	Standard
Hydraulic Tank Capacity	44 (L) 11.62 (gallons)
Standard Wheels	180 mm Rubber Tracks
Electrical system (V)	12
Battery capacity(Ah)	45
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	771.62 (with counterweights)
Lift Height to Pin (in.)	80.4
Traction Force (LBS)	1510.17 (with counterweights)
Breakout Force (LBS)	705.48
Dimensions (L in. x W in. x H in.)	60.04x41.34x51.38
Weight (LBS)	1829.84
Case Drain	Included

TL11E ELECTRIC



TL11E	Standard Setup
Motor	Dana Electric Motor
Revolutions per minute	2500
Battery Type	Traction battery
Voltage (V)	36
Battery capacity (Ah)	240
Engine power (KW)	5.7
Drive System	Hydraulic 4WD wheel motors*
Speed	4.9 km/h / 3.045 mph
Hydraulic Drive System	4.8 GPM
Hourmeter	Standard
Hydraulic Tank Capacity	18 (L) 4.76 (gallons)
Standard Wheels	7 in. Rubber Tracks
Braking System	Hydraulic with 4 wheel motors
Steering	Skid Steering
Lifting Capacity (LBS)	992.08 (with counterweights)
Traction Force (LBS)	859.80 (with counterweights)
Breakout Force (LBS)	881.85
Dimensions (L in. x W in. x H in.)	60.04x41.34x51.38
Weight (LBS)	2314.85

*High power wheel motors

Charger (apart)	
Electronic charger (code 48161020)	220V

TL SERIES OPTIONS

- Case Drain (TL11E)
- Floating System
- Electric Floating Systems
- Integrated Counterweights (50kg)
- Side Counterweights (30kg)
- Electric Socket + Flow Diverter Kit
- LED Working Lights
- Canister Filter
- Toro Plate Adapter



Authorized Distributor

3950 Steffler Rd., Elmira Ontario, N3B 2Z3

Toll Free: 855-664-2752

Tel: 519-664-2752

Email: sales@mkmartin.ca

www.mkmartin.ca

